The listing of claims will replace all prior versions and listings of claims in the

application:

**Listing of Claims:** 

1. (Currently Amended) A device for engaging tissue, comprising:

a generally-annular-shaped body defining a plane and disposed about a central axis

extending substantially normal to the plane, the body being movable from a substantially planar

configuration lying generally in the plane towards a transverse configuration extending out of the

plane, the body being biased to return toward the planar configuration from the transverse

configuration, the body comprising a plurality of looped elements comprising alternating first

and second curved regions;

at least one first primary tine extending from a first curved region of a looped element of

the annular-shaped body generally towards the central axis in the planar configuration and being

deflectable out of the plane when the body is moved towards the transverse configuration;

at least one second primary tine extending from another first curved region of a looped

element of the annular-shaped body towards the first primary tine when the body is disposed in

the planar configuration; and

said first and second primary tines being offset from and substantially parallel to an axis

of symmetry of the looped element from which they extend, said first and second primary tines

being substantially parallel to each other.

2. (Original) The device of claim 1, wherein the body is biased towards the planar

configuration for biasing the primary tines generally towards the central axis.

3. (Previously Presented) The device of claim 1, further comprising:

a set of secondary tines having lengths shorter than a first length of the at least one first

primary tine and a second length of the at least one second primary tine, the secondary tines

extending from the annular-shaped body generally towards the central axis in the planar

configuration and being deflectable out of the plane when the body is moved towards the

transverse configuration.

Application No. 10/787,073

Amendment "C" dated May 7, 2009

Reply to Office Action mailed November 12, 2008

4. (Original) The device of claim 1, wherein the first primary tine, the second primary

tine, and the body are formed from a single sheet of material.

5. (Original) The device of claim 4, wherein the sheet of material comprises a

superelastic alloy.

6. (Original) The device of claim 1, wherein the looped elements generally define an

endless zigzag pattern extending about the central axis.

7. (Original) The device of claim 1, wherein the first primary tine and the second

primary tine extend from first curved regions disposed opposite one another.

8. (Previously Presented) The device of claim 7, further comprising a set of

secondary tines having lengths shorter than a first length of the at least one first primary tine and

a second length of the at least one second primary tine, the secondary tines extending from the

annular-shaped body generally towards the central axis in the planar configuration and being

deflectable out of the plane when the body is moved towards the transverse configuration, each

pair of adjacent tines having a first curved region disposed therebetween.

9. (Original) The device of claim 8, wherein a secondary tine is disposed on either side

of the first primary tine, and a secondary tine is disposed on either side of the second primary

tine.

10. (Original) The device of claim 1, wherein the plurality of looped elements are

expandable between expanded and compressed states for increasing and reducing, respectively, a

periphery of the body in the transverse orientation.

11. (Original) The device of claim 10, wherein the plurality of looped elements are

biased towards the compressed state.

Application No. 10/787,073

Amendment "C" dated May 7, 2009

Reply to Office Action mailed November 12, 2008

12. (Previously Presented) The device of claim 1 wherein said first and second

primary tines are connected to said first curved regions of said looped elements by a connector

element.

13. (Original) The device of claim 12 wherein said connector element is curved.

14. (Original) The device of claim 12 wherein said connector element is straight.

15. (Original) The device of claim 6 wherein the endless zigzag pattern comprises a

generally sinusoidal pattern.

16. (Original) The device of claim 1 wherein said first curved regions define an inner

periphery of the body and the second curved regions define an outer periphery of the body when

the body is in the planar configuration.

17. (Currently Amended) A device for engaging tissue, comprising:

a generally annular-shaped body defining a plane and disposed about a central axis

extending substantially normal to the plane, the body being movable from a substantially planar

configuration lying generally in a plane towards a transverse configuration extending at an angle

through the plane, the body being biased to return to the planar configuration from the transverse

configuration, the body comprising a plurality of looped elements comprising alternating first

and second curved regions, the first curved regions defining an inner periphery of the body and

the second curved region defining an outer periphery of the body when it is in the planar

configuration;

at least one first primary tine extending from a first curved region generally toward the

central axis in the planar configuration and being deflectable out of the plane when the body is

moved towards the transverse configuration;

at least one second primary tine extending from another first curved region towards the

central axis and being deflectable out of the plane when the body is moved towards the

transverse configuration; and

said first and second primary tines being offset from and substantially parallel to an axis

of symmetry of the looped element from which they extend, said first and second primary tines

being substantially parallel to each other.

18. (Original) The device of claim 1 wherein at least one of said first and second primary

tines is connected to a first curved region by a curved connecting element.

19. (Original) The device of claim 17 wherein at least one of said primary tines is

connected to a first curved section by a straight connecting element.

20. (Original) The device of claim 1 wherein the primary tines overlap the first curved

region which is opposite the first curved region from which the primary tine extends.

21. (Original) The device of claim 17 wherein the primary tines overlap the first curved

region which is opposite the first curved region from which the primary tine extends.

Application No. 10/787,073 Amendment "C" dated May 7, 2009 Reply to Office Action mailed November 12, 2008

- 22. (Original) The device of claim 14 wherein the primary times overlap the first curved region which is opposite the first curved region from which the primary time extends.
- 23. (Original) The device of claim 19 wherein the primary tines overlap the first curved region which is opposite the first curved region from which the primary tine extends.